

Industrial Plates

Product description: It is used for insulation of very high temperatures, industrial facilities, process equipment, steel construction structures, all kinds of technical details requiring heat insulation and fire safety.

Application areas

It is used for heat, sound and fire insulation in steel constructions, industrial plants, process equipment.

Application principles

Application surfaces; After the insulation is made ready for the coating by means of hanging pins or carrier hoops, the plates are installed and the sheet metal coatings are made. It is also used in ready panel applications of industrial plates

Product Code	Density	Thickness	Size	Package			
	kg / m³	mm	mm x mm	piece	m²		
TWSL7030	70	30	600 x 1200	15	10.80	1.666	2.833
TWSL7040	70	40	600 x 1200	12	8.64	1.250	2.125
TWSL7050	70	50	600 x 1200	8	5.76	1.000	1.700
TWSL7060	70	60	600 x 1200	6	4.32	833	1.416
TWSL7070	70	70	600 x 1200	6	4.32	715	1.214
TWSL7080	70	80	600 x 1200	5	3.60	625	1.063
TWSL70100	70	100	600 x 1200	4	2.88	500	850
TWSL70120	70	120	600 x 1200	4	2.88	416	700
TWSL10030	100	30	600 x 1200	8	5.76	1.666	2.833
TWSL10040	100	40	600 x 1200	6	4.32	1.250	2.125
TWSL10050	100	50	600 x 1200	4	2.88	1.000	1.700
TWSL10060	100	60	600 x 1200	4	2.88	833	1.416
TWSL10070	100	70	600 x 1200	3	2.16	715	1.214
TWSL10080	100	80	600 x 1200	4	2.88	625	1.063
TWSL100100	100	100	600 x 1200	3	2.16	500	850
TWSL100120	100	120	600 x 1200	2	1.44	416	700
TWSL11025	110	25	600 x 1200	10	7.20	2.000	3.400
TWSL11030	110	30	600 x 1200	8	5.76	1.666	2.833
TWSL11040	110	40	600 x 1200	6	4.32	1.250	2.125
TWSL11050	110	50	600 x 1200	4	2.88	1.000	1.700
TWSL11060	110	60	600 x 1200	4	2.88	833	1.416
TWSL11070	110	70	600 x 1200	4	2.88	715	1.214
TWSL11080	110	80	600 x 1200	4	2.88	625	1.063
TWSL110100	110	100	600 x 1200	3	2.16	500	850
TWSL110120	110	120	600 x 1200	2	1.44	416	700

Reminders on Loading, Unloading, Transport and Storage:

- ▶ It should be done in closed areas in rainy weather.
- ▶ Stretch the canvas even when they are shipped for short distances.
- ▶ It should be stored in the package and the damaged package should not be used.
- ▶ Packages should not be stacked on top of each other.
- ▶ The products are not be stepped on or used as a step.
- ▶ Before pulling with rope, hard cardboard with dimensions of 50x20 cm size should be placed under the rope.
- ▶ Storage area should be closed to prevent leakage during rain, flooding etc.
- ▶ The storage floor must be flat and non-slippery.
- ▶ Loading and unloading should be done with the roof crane.
- ▶ Plates should be carefully transported to the application area by two persons.



terraWOOL
101 | SES | YANIKIN